

ACTUATION: NEW PRODUCT ANNOUNCEMENT

**READY
TO
ORDER!**



SERIES 19 S400 ELECTRIC ACTUATORS

TORQUE OUTPUT
Up to 3540 in-lbs

COMPACT PROFILE

Compact, NEMA 4X enclosure, perfect for OEM and skid manufacturers

MULTI-VOLTAGE CAPABILITY

95 VAC to 265 VAC or 24 VAC/VDC

REVERSING, BRUSHLESS DC MOTOR

Overall lower cycle time compared to traditional brushed motor

LOCAL CONTROLS

Used with OLED and push buttons, a user can locally open or close units via a password

75% DUTY CYCLE

Ideal for high cycling applications

WARRANTY

Industry-leading 3-year warranty

SERIES 19 ACTUATOR SELECTION CHART

Valve	Valve Size	C20	S20	S50	S110	S400
Type-14 Diaphragm Valve [24 VAC/VDC]	1/2" - 1-1/4"		X			
	1-1/2" - 4"			X		
Type-14 Diaphragm Valve [95-265 VAC]	1/2" - 4"			X		
Type-C Gate Valve	1-1/2" - 4"			X		
Type-27 Omni® Ball Valves	3/8" - 2"	X				
Type-21/21a SST Ball Valves	1/2" - 2"	X	X			
	2-1/2" - 3"			X		
Type-23 Multiport® Valves	4"				X	
	1/2" - 2"	X	X			
	3"			X		
Type-57P Butterfly Valves	4"				X	
	1-1/2" - 2-1/2"		X			
	3" - 4"			X		
	5" - 6"				X	
	8" - 10"					X

S400 shown on an 8" butterfly valve.