

The Polymatic Electrofusion Welding Equipment

The Polymatic is suitable for all electrofusion fittings requiring up to 48 volts. All parameters are set using a bar code input device. Automated control of all welding parameters insures safe and reliable fusion. The entire tool features a tough thermoplastic housing that resists damage due to moisture.

The Polymatic welds both HDPE and Polypropylene.

Features:

All Electrofusion Fittings up to 48 Volts.
Parameters are Set Using a Bar Code
Safe and Reliable Fusion.
Tough Thermoplastic Housing that Resists
Damage Due to Moisture.



Includes:

Base Equipment
Rotational Scraper 25-110mm or 110-225mm
(Please Specify Scraper Size)
Extra Scraper Blades
Bar Code Reader
Crate: 21" x 27" x 19" / with Pallet 48" x 40 " x 23"
Weight: 100 lbs / with Pallet 150 lbs.
110 Volt Power Supply

Part Number: 5830000
List Price \$9,100.00*

Available for Rental
Part Number: 9830000
Rental Rates: See Page 21

*Purchase price does not include scraper. See page 13 for scraper list prices.

Options:

DESCRIPTION	PART #	PRICE
Scaper Blade (1 pc/set)	5831000	96.95

Hot Air Welder 700 R

Features:

Built in Motor with Air Cooler
Adjustable from 20 - 600°C (68-1112°F)

Includes:

115 Volt 700 Watt Welder
Combination Speed/tacking Tip (4" mm)

Options:

DESCRIPTION	PART #	PRICE
Round Tip	5641000	95.00
Combo Speed/Taking Tip	5642000	168.00
Spare Heating Unit	5645000	225.00



Part Number: 5638000
List Price \$1,175.00

Available for Rental
Part Number: 9638000
Rental Rates: See Page 21