

Fast Pack - Valve/Actuator Packages

**SHIPS IN
24 HRS !**



Series 92/Type-57P Butterfly Valve

Standard Features (Sizes 1-1/2" - 8")

- UL-508 listed electric actuator
- Type-57P PVC body, PP disc, EPDM or FKM seals, wafer style
- 120 VAC capacitor-run reversing type motor
- Thermal overload protection with auto reset
- Declutchable manual override
- Visual beacon position indicator
- 15 second cycle time* 1-1/2" - 4", 32 second cycle time 6" and 8" Type-57
- Mechanical brake supplied as standard for 6" and 8" Type-57P
- Weatherproof enclosure rated Type 4X. with thermally bonded powder coat finish and stainless steel trim
- RHM module [consists of 2-SPDT 8A relays/dry contacts and heater and thermostat] [see page 71]
- PPG mounting bracket with 304 stainless steel coupling and hardware, 304 stainless steel mounting bracket, coupling and hardware sizes 6" and 8"
- Complete factory assembled and tested actuated valve package

**SHIPS IN
24 HRS !**



Series 92/Type-21 Ball Valve

Standard Features (Sizes 1/2" - 4")

- UL-508 listed electric actuator
- Type-21 PVC with EPDM or FKM seals, true union ball valve
- Type-21 1/2" - 2" supplied with both socket and threaded ends, 2-1/2" - 4" socket only
- 120 VAC capacitor-run reversing type motor
- Thermal overload protection with auto reset
- Declutchable manual override
- Visual beacon position indicator
- 15 second cycle time*
- Weatherproof enclosure rated Type 4X. with thermally bonded powder coat finish and stainless steel trim
- RHM module [consists of 2-SPDT 8A relays/dry contacts and heater and thermostat] [see page 71]
- PPG mounting bracket with 304 stainless steel coupling and hardware
- Complete factory assembled and tested actuated valve package

| Valve Type | Size | Actuation Model | Input Voltage | L.R. Amps | Duty Cycle |
|------------|-----------|-----------------|---------------|-----------|------------|
| Type-21 | 1/2 - 3 | S92RHMW | 120 VAC | 0.5 | 100% |
| Type-21 | 4 | A92RHMW | 120 VAC | 0.8 | 75% |
| Type-57P | 1-1/2 - 4 | S92RHMW | 120 VAC | 0.5 | 100% |
| Type-57P | 6 | B92BRRHMW | 120 VAC | 0.8 | 100% |
| Type-57P | 8 | C92BRRHMW | 120 VAC | 1.0 | 50% |

*Cycle times approximate. Duty cycle shown for ambient temp. (73° F)